

# TECHNICAL DATA SHEET

## XMP 20W-50



### DESCRIPTION

XMP Motor Oil is a 20W-50 motor oil ideally suited to vehicles (1998 or earlier), requiring a petrol engine oil meeting API SH or lower. For newer vehicles requiring API SL oils, use Hi Tech Premium.

### SUMMARY OF BENEFITS

- Suitable for pre 1999 vehicles
- Low Phosphorus content will not harm catalytic converter exhaust systems
- Can also be used for lubrication of lightly loaded diesel engines

### SPECIFICATIONS

- SAE VISCOSITY 20W-50
- MIL-L-46152B
- API SH, CD
- FORD ESE-M2C-153E
- GM 6048M

### SUITABLE FOR



XMP 3	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.8865
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	163
@ 100°C	ASTM D445	cSt	18.5
VISCOSITY INDEX	ASTM D2270	-	125
POUR POINT	ASTM D97	°C	-16
FLASH POINT (COC)	ASTM D92	°C	>205

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

### STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

### AVAILABLE PACK SIZES

205LT - #30022, 20LT - #32022 AND 4LT - #30422

February 2022

**GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD**

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747  
Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au