



**100** Celebrating  
**YEARS**

**AUSTRALIAN OWNED AND TRUSTED SINCE 1926** 

# CHAIN SAW BAR OIL

Last updated: 20/02/2026 3:58 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
CSB001	1L	6
CSB004	4L	4
CSB020	20L	
CSB205	205L	

## PRODUCT BENEFITS

**Chain Saw Bar Oil** is a specially formulated tacky lubricant designed to protect the chain and bar of all types of chainsaws against premature wear, rust & corrosion.

**Please Note:** Chain Saw Bar Oil 4Lt (CSB004) supercedes Chain Saw Bar Oil 5 Lt (CSB005)

## APPLICATION

**Chain Saw Bar Oil** is suitable for all petrol and electric type chainsaws to flush away dust, chips and sap from working surfaces ensuring smooth and consistent cutting. Keeps chains sharper for longer and provides lubrication for the sprocket, bar and chain. It provides a barrier against moisture preventing corrosion and its tacky formulation reduces throw off and flinging off the chain during operation, This reduces wastage and provides better economy over normal engine type oils.

## HOW TO USE

Add directly to the chain bar oil reservoir for automatic lubrication systems but can also be used manually on the chain if needed for added lubrication & protection.

## SUITABLE FOR THE FOLLOWING TYPES OF CHAINSAWS -

Black & Decker	Dolmar	Echo	Hitachi
Homelite	Honda	Husqvarna	Jonsered
John Deere	Kawasaki	Komatsu	Makita
McCulloch	MTD	Oleo-Mac	Ozito
Poulan	Ryobi	Shindaiwa	Stihl
Talon	Tanaka	Briggs & Stratton	Oregon
Craftsman	Yukon	Partner	EFCO
Skil	Bosch	Redmax	Earthquake
Wuhan	Olympyc	Delshine	Duramark

and many others requiring bar & chain lubrication

**Please Note:** A 58mm cap with pouring tap is available to fit 20 litre packs.  
<https://penriteoil.com.au/products/58mm-plastic-tap>

## PRODUCT BENEFITS

- Tacky additives reduce throw or fling off
- Lubricates chain, bar & sprocket
- Special additive system reduces wear of components
- Flushes chips, dust and sap from the working surfaces
- Blades remain sharper for longer periods
- Provides corrosion protection to chain and bar
- Suitable for electric and petrol type chainsaws

## PRODUCT PERFORMANCE LEVELS

- ISO 125





**100** *Celebrating*  
**YEARS**

**AUSTRALIAN OWNED AND  
TRUSTED SINCE 1926** 

**TYPICAL DATA**

Colour	Dark Blue
ISO Grade	125
Density at 20°C, kg/L	0.889
Viscosity, Kinematic, cSt at 40°C	128
Viscosity, Kinematic, cSt at 100°C	13.6
Viscosity Index	102
Zinc, Mass %	0.032